


PPLQB0110 02 09014-H0 DE 3500lm



PRODUCT DESCRIPTION

APPLICATION:	Offices, meeting rooms Shops, commercial areas. General-purpose areas, with no specific risks Suspended luminaire
MATERIALS EXECUTION:	Extruded anodized aluminium profile body. Reflector metalized nylon Reflector injected, bright metallic
MAINS SUPPLY AND WIRING	Voltage and frequency supply of the luminaire (230V at 50Hz). Luminaire wired with electronic driver. Quick Attach System. Luminaire supplied with light source incorporated.
ACCESSORIES	SIS 500 mm, SIS 1000 mm, SIS 1500 mm, SIS-AN 500 mm, SIS-AN 1000 mm, SIS-AN 1500 mm, SISL-AN 500mm, SISL-AN 1000mm, SISL-AN 1500mm, 3-pole power supply connector.
OPTIONS	Luminaire wired with electronic driver for dimming, BlackTextured gray / RALT 9005 (on request), White Textured/ RALT 9016 (on request).

TECHNICAL DATA

	Luminous Flux (Lm)	System Power (W)	Luminous Efficacy (lm/W)	LED Risk Group	Colour Temp. (K)	UGR		Dimensions (mm)				
						(X= 4H; Y= 8H; S= 0,25H)		Length	Width	Height	Fixation	Suspension
						Tran.	Long.					
PPLQB0110 02 09014-H0 DE 3500lm	2853	18,7	153	2	4000	16.8	16.9	846	70	75	n/a	755


OTHER TECHNICAL INFORMATION

CRI: > 80

Photometric Code: 840/359

Lifetime Factor (L70B10) @ Ta=25°C: 50.000 h

POLAR DIAGRAM



ENERGY LABEL

NORMS

EN 60598-1, EN 60598-2-22, EN 55015, EN 61000-3-2, EN 61547, 2014/30/EU, 2014/35/EU, 2011/65/EU (RoHS), (EU) N° 1194/2012 (Ecodesign), EN 60598-2-1