




Technical Data Sheet

PULG 03 12014-C9 DE 2110lm RALT 9005



PRODUCT DESCRIPTION





APPLICATION: Offices, meeting rooms
Shops, commercial areas.
Supermarkets
General-purpose areas, with no specific risks
Suspended luminaire

MATERIALS EXECUTION: Extruded anodized aluminium profile body.
Die-cast aluminum end-caps.
Polycarbonate Grid with PMMA lens

MAINS SUPPLY AND WIRING: Voltage and frequency supply of the luminaire (230V at 50Hz).
Luminaire wired with electronic driver.

ACCESSORIES: FA 500 mm, FA 1000 mm, FA 1500 mm, SIS 500 mm, SIS 1000 mm, FA-AN 500 mm, FA-AN 1000 mm, SIS 1500 mm, SIS-AN 500 mm, FA-AN 1500 mm, FAC 500 mm, SIS-AN 1000 mm, SIS-AN 1500 mm, FAC 1000 mm, FAC 1500 mm, SISL-AN 500mm, SISL-AN 1000mm, FAC-AN 500 mm, FAC-AN 1000 mm, SISL-AN 1500mm, FAC-AN 1500 mm.

OPTIONS: Luminaire wired with electronic driver for dimming, Luminaire equipped with emergency kit 1H, Luminaire suitable for looping-in connection.



TECHNICAL DATA

	Luminous Flux (Lm)	System Power (W)	Luminous Efficacy (lm/W)	LED Risk Group	Colour Temp. (K)	UGR		Dimensions (mm)				
						(X= 4H; Y= 8H; S= 0,25H)		Length	Width	Height	Fixation	Suspension
						Tran.	Long.					
PULG 03 12014-C9 DE 2110lm RALT 9005	1825	15,0	122	1	4000	09.9	10.9	1156	50	56	n/a	1080


OTHER TECHNICAL INFORMATION

CRI: > 80


Photometric Code: 840/3XX

Lifetime Factor (L70B10) @ Ta=25°C: 50.000 h

POLAR DIAGRAM



ENERGY LABEL



NORMS

EN 60598-1, EN 55015, EN 61000-3-2, EN 61547, 2014/30/EU, 2014/35/EU, 2011/65/EU (Rohs), (EU) N° 1194/2012 (Ecodesign), EN 60598-2-1