

PRODUCT DESCRIPTION

Applications: Shops, commercial areas; Supermarkets; Public areas, corridors; warehouses, storage rooms


Execution: Soft steel sheet body, with anti-corrosion treatment; White coated body. UV protected.; Die-cast aluminum end-caps; For QL trunking System.

Light Distribution: Direct lighting;

Light Source: Fluorescent Lamp T5.

Optics: QLCMI - Semi Opal flat diffuser in PMMA.

QLCMX – Parabolic reflectors anodized aluminum semiespecular high yield, with high coefficient of reflection and without iridescence.



| Reference | Article | Length | Width | Height | W |
|-----------------|---------------------|--------|-------|--------|---------|
| QLCMI 01 121 BE | 11QB7SR001R32005121 | 950mm | 164mm | 60mm | 22,5 W |
| QLCMI 01 221 BE | 11QB7SR001R32005221 | 950mm | 203mm | 60mm | 45,5 W |
| QLCMX 01 139 BE | 11QB7SR001R32005139 | 950mm | 164mm | 60mm | 40,4 W |
| QLCMI 01 239 BE | 11QB7SR001R32005239 | 950mm | 203mm | 60mm | 83,4 W |
| QLCMI 01 128 BE | 11QB7SR001R32005128 | 1250mm | 164mm | 60mm | 30,5 W |
| QLCMX 01 228 BE | 11QB7SR001R32005228 | 1250mm | 203mm | 60mm | 61 W |
| QLCMI 01 154 BE | 11QB7SR001R32005154 | 1250mm | 164mm | 60mm | 57,7 W |
| QLCMI 01 254 BE | 11QB7SR001R32005254 | 1250mm | 203mm | 60mm | 114,5 W |
| QLCMX 01 121 BE | 11QB8SR001R32005121 | 950mm | 164mm | 60mm | 22,5 W |
| QLCMX 01 221 BE | 11QB8SR001R32005221 | 950mm | 203mm | 60mm | 45,5 W |
| QLCMX 01 139 BE | 11QB8SR001R32005139 | 950mm | 164mm | 60mm | 40,4 W |
| QLCMI 01 239 BE | 11QB8SR001R32005239 | 950mm | 203mm | 60mm | 83,4 W |
| QLCMX 01 128 BE | 11QB8SR001R32005128 | 1250mm | 164mm | 60mm | 30,5 W |
| QLCMX 01 228 BE | 11QB8SR001R32005228 | 1250mm | 203mm | 60mm | 61 W |
| QLCMX 01 154 BE | 11QB8SR001R32005154 | 1250mm | 164mm | 60mm | 57,7 W |
| QLCMX 01 254 BE | 11QB8SR001R32005254 | 1250mm | 203mm | 60mm | 114,5 W |

Accessories

EXTENSION CABLE (Installed)



Superior View