



PRODUCT DESCRIPTION

Applications: Emergency exits.

Assembly: Suspended luminaire; Ceiling surface-mounted luminaire; For QL trunking system.

Light Distribution: Direct.


Fonte de Luz: LED 4000K , C R I > 80 , L70B10-50000h.

Execution: Extruded anodized aluminium profile body.;

Pictogram included.;; Injected V0 polycarbonate end-caps.;

Maximum rotation angle 90°;

Optics: Luminaire with semiopaline acrylic film;



Reference	Article	Length	Width	Height	W
QLELEL 01 04014-A6 NM/60m	11QA9SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/60m ST	11QB0SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 NM/60m PRO	11QB1SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 M/60m	11QB2SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/180m	11QB3SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/180m ST	11QB4SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 NM/180m PRO	11QB5SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 M/180m	11QB6SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/60m (EN7010)	11QC1SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/60m ST (EN7010)	11QC2SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 NM/60m PRO (EN7010)	11QC3SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 M/60m (EN7010)	11QC4SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/180m (EN7010)	11QC5SR001R51001K15	420mm	55mm	264mm	5,8W
QLELEL 01 04014-A6 NM/180m ST (EN7010)	11QC6SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 NM/180m PRO (EN7010)	11QC7SR001R51001K15	420mm	55mm	264mm	4,8W
QLELEL 01 04014-A6 M/180m (EN7010)	11QC8SR001R51001K15	420mm	55mm	264mm	5,8W

QLELEL mains supply must be specific and different from the lighting fittings



Pictogram Rule 92/58/CEE



Pictogram EN7010