


GBL

HIGH BAY LUMINAIRE



De acordo com EN60 598-2-1



Product Description

Applications

Industry; Warehouses, storage rooms; Sport halls; Work-shops, assembly halls.

Light Distribution

Direct lighting;
LE— Wide light distribution;
LI — Narrow light distribution;
XE— Wide light distribution;
XI — Narrow light distribution;

Installation

Suspended luminaire; Ceiling surface-mounted luminaire.

Optics

Luminaire with tempered glass;
LI/LE— PMMA lens;
XI/XE— Parabolic reflectors anodized aluminium semi-specular high yield, with high coefficient of reflection and without iridescence.

Execution

Injected aluminium body.

Options

Luminaire wired with electronic driver for dimming; Luminaire equipped with emergency kit; Luminaire suitable for looping-in connection.


Accessories

Fixing Kit: GBL Fixing Kit.


Ref.	Art.	H _(mm)	D _(mm)	LE Luminous Efficiency	SD System Power
GBL/LE 01 05054-M0 DE 30498lm RALT 9006	11246SR001R66005N67	115	500	128 lm/W	204,5 W
GBL/LE 01 05054-M0 DE 25415lm RALT 9006	11246SR001R66005N68	115	500	129 lm/W	171,0 W
GBL/LE 01 05054-M0 DE 20332lm RALT 9006	11246SR001R66005N69	115	500	130 lm/W	137,5 W
GBL/LE 01 05054-M0 DE 15249lm RALT 9006	11246SR001R66005N70	115	500	128 lm/W	104,0 W
GBL/LI 01 05054-M0 DE 30498lm RALT 9006	11247SR001R66005N67	115	500	128 lm/W	204,5 W
GBL/LI 01 05054-M0 DE 25415lm RALT 9006	11247SR001R66005N68	115	500	129 lm/W	171,0 W
GBL/LI 01 05054-M0 DE 20332lm RALT 9006	11247SR001R66005N69	115	500	130 lm/W	137,5 W
GBL/LI 01 05054-M0 DE 15249lm RALT 9006	11247SR001R66005N70	115	500	128 lm/W	104,0 W
GBL/XE 01 05054-M0 DE 30498lm RALT 9006	11240SR001R66005N67	115	500	128 lm/W	204,5 W
GBL/XE 01 05054-M0 DE 25415lm RALT 9006	11240SR001R66005N68	115	500	129 lm/W	171,0 W
GBL/XE 01 05054-M0 DE 20332lm RALT 9006	112460R001R66005N69	115	500	130 lm/W	137,5 W
GBL/XE 01 05054-M0 DE 15249lm RALT 9006	112460R001R66005N70	115	500	128 lm/W	104,0 W
GBL/XI 01 05054-M0 DE 30498lm RALT 9006	11245SR001R66005N67	115	500	128 lm/W	204,5 W
GBL/XI 01 05054-M0 DE 25415lm RALT 9006	11245SR001R66005N68	115	500	129 lm/W	171,0 W
GBL/XI 01 05054-M0 DE 20332lm RALT 9006	11245SR001R66005N69	115	500	130 lm/W	137,5 W
GBL/XI 01 05054-M0 DE 15249lm RALT 9006	11245SR001R66005N70	115	500	128 lm/W	104,0 W



GBL HIGH BAY LUMINAIRE



LI/LE PMMA LENS ☀




XE/XI PARABOLIC REFLECTORS ☀




EYE BOLT INCLUDED




GBL FIXING KIT




GBL/LE 01 05054-M0 15249lm



GBL/LI 01 05054-M0 15249lm



GBL/XE 01 05054-M0 15249lm



GBL/XI 01 05054-M0 15249lm