


PULG

SUSPENDED LUMINAIRE



According to EN60 598-2-1



Product Description

Applications

Offices, meeting rooms; Shops, commercial areas; General-purpose areas, with no specific risks.

Light Distribution

Direct distribution; UGR <13.

Installation

Suspended luminaire.

Optics

Polycarbonate Grid with PMMA lens.

Execution

Extruded anodized aluminium profile body; Die-cast aluminum end-caps.

Options

Luminaire with dimmable electronic driver.

Light Source

LED 4000K, CRI > 80, 50.000h@ L70B10, Ta=25.

Ref.

PULG 03 12014-C9 DE 2110lm RALT 9005

PULG 03 18014-C9 DE 3165lm RALT 9005

PULG 03 23014-C9 DE 4220lm RALT 9005

Art.

11239SR003R68005K41

11239SR003R68005K42

11239SR003R68005K43

L mm	W mm	H mm	SP System Power	LE Luminous Efficiency	SP System Power
1156	47	56	1080	96 lm/W	14,2 W
1726	47	56	825-825	100 lm/W	21,3 W
2296	47	56	740-740-740	106 lm/W	28,4 W

Accessories

Suspensions

SIS

SIS-AN

SISL-AN

L
mm

500; 1000; 1500

500; 1000; 1500

500; 1000; 1500



PULG SUSPENDED LUMINAIRE



POLYCARBONATE GRID WITH PMMA LENS ✨



FA-AN KIT



FA KIT




SIS-AN SUSPENSION



SIS SUSPENSION



SISL-AN SUSPENSION



PULG 03 23014-C9 DE 4220lm